



SMCANT-LP
EliteConnect™ 2.4/5GHz Lightning Surge Protector

TECH SPECS

FREQUENCY RANGE

- 0-6 GHz

CONNECTOR TYPE

- N TYPE

IMPEDENCE

- 50 Ohms

V.S.W.R.

- <1.5:1

INSERTION LOSS

- 0.6dB

MAXIMUN HANDLING POWER

- 10W

INSULATION RESISTANCE

- DC 100V MORE THAN 50M O

D.C. DISCHARGE VOLTAGE

- DC 230V ±20%

INITIAL IMPULSE WAVE DISCHARGE VOLTAGE

- LESS THAN 700V 1KV /μ sec

RATED IMPULSE WAVE DISCHARGE

- 10KA 8/20 μ sec 5 times

WORKING TEMPERATURE

- -30°C ~ +85°C

DIMENSIONS

- 2.5 (L) x 1 (W) x 1.25 (H) in
- 63.5 (L) x 25.4 (W) x31.75 (H) mm

CONTACT

North America
20 Mason
Irvine, CA 92618
1-800-SMC-4YOU
24/7 Technical Support

Europe/Africa
Fructuos Gelabert 6-8
08970 Sant Joan Despí
Barcelona, Spain

Check www.smc.com for your local country contact information

© 2008 SMC Networks. SMC and the SMC logo are registered trademarks of SMC Networks in the United States or other countries. Other trademarks or registered trademarks are the property of their respective owners. Information is subject to change without notice. All rights reserved.

12/2008