

## SMCDSP-205 TigerVoIP™ Desktop SIP Phone



### OVERVIEW

The SMC TigerVoIP™ Desktop Phone (SMCDSP-205) is compliant with the SIPv2 Voice over Internet Protocol (VoIP) and can be used with a SIP based Internet Telephony Service Provider (ITSP), IP PBX and other SIP based client devices to make and receive VoIP calls anywhere you have internet access. When used with an ITSP both home and business users can take advantage of reduced rate calls to the traditional telephone network, and generally free calls over the Internet.

For small businesses the SMCDSP-205 can be used with SMC's TigerVoIP™ IP PBX (SMCPBX10). This allows you to take advantage of free calls between branch offices located around the world as well as reduced rate calls to the traditional telephone

network. Increased functionality is added with supplementary services such as Call Waiting, Call Hold, Call Resume, Call Transfer, Call forwarding and 3-way conference calling. You can also centrally manage VoIP user accounts and automatically provision these settings to phones.

The SMCDSP-205 has a stylish and functional design. It includes a LCD display, 10 feature keys, programmable speed dials, a speaker phone and two 10/100Mbps Ethernet ports. The two 10/100Mbps Ethernet ports allow you to connect the phone and a PC using a single network point. Configuring the SMCDSP-205 via the keypad and web based management interface is intuitive making the phone easy to setup and manage.

FEATURES	BENEFITS
SIPv2 compliant	The SMCDSP-205 can be used with a SIP based Internet Telephony Service Provider (ITSP), IP PBX and other SIP based client devices to make and receive low cost VoIP calls.
Supplementary services	Supplementary services such as Call Waiting, Call Hold, Call Resume, Call Transfer, Call forwarding and 3-way conference calling provide increased functionality at no extra cost.
Superb voice quality	Advanced Digital Signal Processing (DSP), Silence suppression, VAD, CNG and AEC provide superb voice quality.
2-port 10/100Mbps switch	The two 10/100Mbps Ethernet ports allow you to connect the SMCDSP-205 and a PC using a single network point.
Auto provisioning**	When used in combination with the TigerVoIP™ IP PBX (SMCPBX10) you can centrally manage VoIP user accounts and automatically provision these settings to the phone. This reduces the need to manually configure each phone.



## TECHNICAL SPECIFICATIONS **SMCDSP-205**

### PHONE FEATURES

- LCD display
- Four way directional key for menu navigation
- Message Waiting Indicator (MWI) light
- Voicemail message retrieval button
- 10 Feature keys
- Volume control button
- Standard 12 button dialling keypad
- Programmable speed dials
- Speaker phone
- Phone book
- Multiple ring tones
- Multiple user accounts - up to 3
- Multiple lines - up to 2
- 2-port 10/100Mbps switch
- VLAN (802.1Q)

### CALL FEATURES\*\*

- Call Waiting
- Call Hold/Resume
- Call Forward
- Call Transfer
- 3-Way Conference Call
- Caller ID
- Call History
- Redial
- Call Recording

### VOICE FEATURES

- SIPv2 (RFC3261)
- SIP INFO (RFC2976)
- SIP RPORT(RFC 3581)
- SDP (RFC2327)
- RTP (RFC1889)
- RTCP (RFC1890)
- G.711u-/a-law\*\*
- G.726\*\*
- G.729A/B\*\*
- G.723.1\*\*
- Voice Activity Detection (VAD)
- Comfort Noise Generation (CNG)
- G.167 Acoustic Echo Cancellation (AEC)
- Adaptive Jitter Buffer (AJB)
- DTMF: In-band and Out-band (RFC2833) (SIP INFO)

### NAT TRAVERSAL

- STUN (RFC3489)
- Outbound Proxy

### MANAGEMENT

- Keypad configuration
- Web based management interface (HTTP)
- Telnet
- Auto provisioning\*\*
- Remote firmware upgrade\*\*

### SECURITY

- HTTP 1.1 Basic/Digest Authentication for web setup
- MD5 for SIP authentication (RFC2069/RFC2617)

### TEMPERATURE

- Operating: 0° degrees C to 40° degrees C
- Storage: -20° degrees C to 70° degrees C

### HUMIDITY

- Operating: 10% to 85% Non-condensing
- Storage: 5% to 90% Non-condensing

### DIMENSION

- 200 x 173 x 108 mm
- 7.9 x 6.8 x 4.3 in

### WEIGHT

- 0.883Kg
- 1.95lbs

### POWER INPUT

- 6V, 1A

### CERTIFICATIONS

- FCC
- CE

### SYSTEM REQUIREMENTS

- Available 10/100Base-T Ethernet port
- A SIP based VoIP user account
- We recommend using this product with the SMCPBX10

### PACKAGE CONTENTS

- One Desktop SIP Phone (SMCDSP-205)
- One handset
- One power adapter
- One RJ-45 Ethernet cable
- Quick Start Guide
- Documentation CD

### WARRANTY

- Limited Lifetime

\*\*Requires network support

## Contact

**North America**  
20 Mason  
Irvine, CA 92618  
1-800-SMC-4YOU  
24/7 Technical Support

**Europe/ Africa**  
Fructuos Gelabert 6-8  
08970 Sant Joan Despí  
Barcelona, Spain

Check [www.smc.com](http://www.smc.com) for your local country contact information